ITEM #0210100A - ANTI -TRACKING PAD

Description:

Work under this item shall consist of furnishing, installing, maintaining and removing a crushed stone anti-tracking pad on filter fabric and returning to the original condition upon completion at the location and details shown on the plans or ordered by the Engineer.

Materials:

Materials for this work shall conform to the requirements of Article M.01.01, No.3 for crushed stone, and Article M.08.01-26 for geotextile filter fabric.

Construction Methods:

Clear area of anti-tracking pad of all vegetation and excavate to a minimum depth of 4". Place geotextile filter fabric over the full width and length of excavated area and cover with No. 3 crushed stone to a depth of no less than 4".

The anti-tracking pad shall be uniformly graded to produce the entry and exit path to the site for all construction equipment. The pad shall be maintained of sufficient grading and stone surface to capture all soils and sediment from equipment tires prior to such exiting from the site.

Stone shall be replenished or replaced as necessary or as ordered by the Engineer to assure sufficient capture of sediment at the construction site. Any sediment tracked off the site shall be immediately cleaned, swept and removed by the Contractor at no cost to the State.

Method of Measurement:

This work will be measured for payment by the number of square yards of accepted antitracking pad completed as shown on the plans or ordered by the Engineer.

Basis of Payment:

This work will be paid for at the contract unit price per square yard for "Anti-Tracking Pad," which price shall include furnishing, placing, maintaining, removing all anti-tracking pad materials and returning location back to the original condition upon completion, equipment, tools and labor incidental thereto as well as cleaning, sweeping any sediment tracked off site. Clearing and grubbing required to install anti-tracking pad be paid under item "Clearing and Grubbing".

Pay Item Pay Unit

Anti-Tracking Pad